

# CONNEX Radiating Clip for RF LLF 1/2"

**RF LLX-CL 1/2"**

**RF LLF Hiflex 1/2"**

**UV Resistant**

**Corrosion Resistant**

**Anti Vibration**

**RoHS and REACH compliant**



**NEK SEALINE**  
Marine Industrial Cables of NEK Kabel AS

Suitable for NEK Sealine  
RF LLF Feeder 1/2"  
RF LLX-CL Leaky 1/2"  
RF LLF Hiflex 1/2"



## Application

Constructed of durable stainless steel, the CONNEX Radiating Clip has been rigorously tested for UV resistance (≥720 hours, ISO 4892.3-1994), corrosion resistance (≥168 hours in a salt spray chamber, IEC 60068-2-11), and vibration survival (≥6 hours, based on IEC 60068-2-6), ensuring consistent electrical performance in all environments. The tool-free design helps support fast and hassle-free installation.

## General Specifications

Cable Type	LLF Feeder   LLX-CL Leaky   LLF Hiflex
Cable Size	1/2"
Material Type	Stainless steel 304
Colour	Silver
Mounting	M8 drilled cable ladder

## Dimensions

Height	1.181 in   30 mm
Width	0.787 in   20 mm
Length	2.165 in   55 mm
Compatible Jacket OD, maximum	0.64 in   16.3 mm
Compatible Jacket OD, minimum	0.54 in   13.7 mm

## Testing & Environmental

Operating Temperature	-40 °C to +85 °C
UV Resistance	≥720 hours, base on ISO4892.3-1994
Corrosion Resistance	≥168 hours in salt spray chamber, base on IEC 60068 -2-11
Anti Vibration	≥6 hours at resonant frequency, base on IEC 60068 -2-6

## Packing Information

Height	1.26 in   32 mm
Width	7.874 in   200 mm
Length	7.874 in   200 mm
Packaging Quantity and UOM	kit of 10
Gross Weight	0.465 lb   0.211 kg
Part Number	CK-9737788



The CONNEK Radiating Clip is recommended to use in conjunction with NEK SEALINE's RF cables.

Explore the cables below for compatible cable solutions

1/2" RF LLF Feeder cable <https://www.nek-sealine.com/en/Product/Details/228603/>

1/2" RF LLX Leaky cable <https://www.nek-sealine.com/en/Product/Details/275257/>

1/2" RF LLF Hiflex cable <https://www.nek-sealine.com/en/Product/Details/212349/>

